




JUWEL Typ OX-Series Mechanical Torque Multiplier

- ° Torque range from 160 to 15,000 Nm
- Repeat accuracy of +/- 2% for the same bolting operation
- Planetary gearbox developed and manufactured 100% in Germany in our own company
- Manually operated, can be used flexibly without hydraulic, pneumatic or electrical energy source
- Supplied in a quality steel case with contoured foam inlay for safe transportation
- Support made of high-strength investment casting individual designs also possible on request thanks to in-house CNC manufacturing

Subject to technical changes and errors.



Technical Data



Тур/Туре	Typ 01RS	Тур 02К	Тур 02	Тур 03	Typ 03L	Тур 04	Тур 06	Тур 07	Тур 08
Antriebsvierkant/Square drive A	1"	1"	1"	1 1/2	1 1/2"	1 1/2"	1 1/2"	1 1/2"	2 1/2"
Artikelnummer/Item number	10 110 000	10 210 000	10 200 000	10 300 000	10 310 000	10 400 000	10 600 000	10 700 000	10 800 000
Drehmoment/Torque (Nm)	160 - 1.200	540 - 3.200	540 - 3.200	540 - 4.200	1.460 - 5.400	680 - 6.200	1.860 - 10.000	1.900 - 12.000	1.900 - 15.000
Eingang	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Gewicht Abstützung/ Weight reaction arm (kg)	1.6	1.6	1.6	3.5	3.5	5.7	5.7	5.7	11
Gewicht/Weight (kg)	3.6	5.9	4.7	5.9	7,5	10,8	15,8	19	31
Höhe/Height C (mm)	55-75	75	75	95	95	110	110	130	145
Höhe/Height H (mm)	180	340	225	235	375	365	315	328	340
Untersetzung/Reducing rate	1:4	1:16	1:16	1:16	1:64	1:22	1:60	1:74,8	1:74,8
Ø Getriebe/Gear D (mm)	85	88	88	88	88	130	130	175	175

More? Follow us!



in Juwel-Schraubtechnik GmbH

► YouTube

@ernstbergersohnejuwel-schr8147